




HENGWEI MICROWAVE

HWSPDT005180A80

FEATURE:

- ◆ Solid State,Mixture Integrated
- ◆ High Speed,Low Loss,High Isolation
- ◆ Field Removable SMA(F) Connector
- ◆ Integrated with Driver



APPLICATION:

- ◆ Test equipment
- ◆ Radar Warfare system
- ◆ Communication system

SPECIFICATIONS

ITEM	Parameter
Fre.	0.5~18GHz
IL (dB.Typ)	3.0dB
Isolation(dB.Min)	80dB
VSWR(Max)	2
Input Power(W.Max)	0.2
Switch time(ns)	50
Current@ +5V/-5VDC(mA.Typ)	60/40
Conector	SMA-K

ENVIRONMENTAL RATINGS


Parameter	Min	Typical	Max	Units
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity		95		%
Altitude	10000		30000	feet
Shock / Vibration(MIL-STD-810F)		Airborne		



HENGWEI MICROWAVE

HWSPDT005180A80


OUTLINE DRAWING(mm)




ON	C
J0-J1	1
J0-J2	0

注: TTL "1" +5V, "0" 0V.

TEST CURVE:



IL



ISO